

LIMITED LIFE PACKAGING

Economical Mamor



- High molecular weight, high-density polyethylene (HDPE), 1.9 specific gravity
- Rigid welded galvanized tubular steel grid, with LABELING plates located on 2 sides
- Pressed galvanized steel base shaped to support the inner container and assist total discharge
- 6" opening with screw cap and "O" ring seal; option viton gasket available
- Complete discharge through 2" poly valve
- UN (31HA1) units



TECHNICAL DATA

DIMENSIONS

Height	45.8"
Base	48"x40"
Weight	138.5 lbs

COMPOSITION

BOTTLE

Net weight	38.5 lbs
Raw material	Lupolen 4261 AG or Finathene 49080 UV
Top opening	6"
Valve connection	standard: 2"
Nominal volume	275 gal.
Total volume	280.5 gal.
Color	standard: natural

VALVE

Butterfly 2"	Gasket: Hostaflon Connection: 2" NPT Camlock 2"
Cylindrical 2"	Gasket: VITON EPDM Connection: 2" NPT

LABELING PLATE

Front and rear	15.75"x19.15"
Option:	15.75"x26.40"

CAP

Standard	6" screw cap: BLACK
Gasket	standard: EPDM Option: VITON

UN APPROVAL

31HA1 / 1.9 specific gravity

OPTIONS:

- Venting with Gore-Tex membrane
- Central 2" screw cap
- Venting with centered PE tap
- 2" Bung NPT

OPTIONS

- EPDM or Viton Gaskets
- 2" cylindrical or butterfly discharge valve
- 1.9 specific gravity polyethylene bottle in galvanized tubular steel grid frame
- UN/DOT authorized



1-800-544-7069



P.O. Box 1171, 8054 McGowin Dr., Fairhope, AL 36533