

STAINLESS STEEL CENTER DISCHARGE

The ECOsafe™ stainless steel IBC UN31A specification permits the shipment of flammable and combustible liquids as authorized by Title 49 CFR.

FEATURES:

- UN/DOT compliant
- 304 stainless steel construction
- Sloped bottom for virtual 100% discharge
- 22" top manway with EPDM gasket and bolted clamp ring
- 3" top fill fitting with fusible cap and lanyard
- 2" top bung fitting
- 2" bottom discharge with lockable stainless steel ball valve

- Stainless steel data plate
- Heavy duty lifting lugs/stackable leg positioners
- Operation decals
- Fork pockets

OPTIONS:

- 316 stainless steel construction
- New & Reconditioned options available



SPECIFICATIONS

CAPACITY* [US GALLONS]	TARE WEIGHT*	LENGTH*	WIDTH*	HEIGHT*
		A	B	C
350 CENTER	598 lbs	42"	48"	53"-56"
550 CENTER	768 lbs	42"	48"	77"-80"
793 CENTER	1041 lbs	54"	54"	80"

*All dimensions, gallons, and weights are nominal.



Believe in better service.

PRECISIONIBC.COM

BROUSSARD, LA
888.805.1247

FAIRHOPE, AL
800.544.7069